

# GV-Multi Quad Card

The GV-Multi Quad Card connects up to 5 TV monitors (spot monitors). One port supports up to 16 screen divisions, while the other 4 ports support 1 and 4 screen divisions. It also allows self-defined channel sequence and position changes of divisions on the monitor screen.

## Packing List

- 1 GV-Multi Quad Card x 1
- 1 1-5 D-Type Video Cable x 1
- 1 40-Pin Ribbon Cable x 1
- 1 Installation Guide x 1

## Specifications

Interface for GV-Video Capture Card	40-pin Connector
TV Output	DB15 to 5 BNC Connectors
Input Singal	16 Channels
TV Monitor Layout	Port 1: supports up to 16 screen divisions. Port 2 ~ Port 5: support 1 and 4 screen divisions.
Compatible Model	GV-250, GV-600, GV-650, GV-800, GV-1120, GV-1240, GV-1480, GV-2004 and GV-2008.
Dimensions	178 mm x 104 mm

## Installing the Drivers:

After you install the GV-Multi Quad Card to the computer, the Hardware Wizard will automatically detect the device. Ignore the Wizard, insert the Software CD, select **Install or Remove GV-Series Driver**, and then click **Install or Remove GV-Series Cards Driver**. When the dialog box appears, click the **Install** button. The card driver will be installed automatically.

When the installation is complete, exit the dialog box.

## Note:

There are no specific system requirements for the GV-Multi Quad Card. Only ensure the computer meets the system requirements by the GV-Video Capture Card installed on that computer.

Use the supplied Ribbon Cable to connect the GV-Multi Quad Card to the GV-Video Capture Card as illustrated below.

